




LED 15W 12" Flush Mount Ceiling

Item # 819
L15FM12PLDIM/40K

1 FIXTURE SPECIFICATION

| | | |
|-----|--------------------------------|-----------------------------------|
| 1-1 | Fixture Type | LED Flush Mount |
| 1-2 | Dimmable (Y/N) | YES (Triac) |
| 1-3 | Fixture Finish/Type | White Plastic frame+Plastic cover |
| 1-4 | Fixture Wattage | 15W |
| 1-5 | Rated Average Life (hours) L70 | 50,000 |
| 1-6 | LED Type | SMD |
| 1-7 | Reliable Operating Temperature | -4F to 113F |



2 Photometric Characteristics

| | | |
|-----|-----------------------------|-------|
| 2-1 | Initial Lumens | 1050 |
| 2-2 | Initial Lumens per Watt | 70 |
| 2-3 | Color Temperature | 4000K |
| 2-4 | Color Rendering Index (CRI) | ≥80 |



3 Electrical Characteristics

| | | | | | |
|-----|------------------------------|-------------|-----|--------------|-----------------|
| 3-1 | Input Line Voltage/Frequency | 120V, 60 Hz | 3-4 | Power Factor | >0.9 |
| 3-2 | Lamp rated Wattage | 15W | 3-5 | Dimming Type | Triac (10-100%) |
| 3-3 | Total Harmonic Distortion | <20% | | | |

4 Dimensional Characteristics

| | | |
|-----|-------------|------|
| 4-1 | Width (mm) | 300 |
| 4-2 | Height (mm) | 96.5 |

5 Product Information

| | | |
|-----|---------------------|---------------------------------------|
| 5-1 | Primary Application | Residential/Hospitality |
| 5-2 | Limited Warranty | 5 Years from date of purchase |
| 5-3 | Certified | ETL/ES/LM79 |
| 5-4 | RoHS Compliant | Yes |
| 5-5 | Environment | Suitable for Damp Location/Indoor Use |

6 Packing Details

| | | | | | |
|-----|---------------|-----------------|-----|-------------------|-----|
| 6-1 | Box size (mm) | 560 x 345 x 350 | 6-3 | Net Weight (Kg) | TBA |
| 6-2 | Qty /Box | 8 pcs | 6-4 | Gross Weight (Kg) | TBA |

01/2017© Overdrive

For more information visit www.overdrive-lighting.com

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.