




LED 15W 12" Flush Mount Ceiling

Item # 819
L15FM12PLDIM/40K

1 FIXTURE SPECIFICATION

1-1	Fixture Type	LED Flush Mount
1-2	Dimmable (Y/N)	YES (Triac)
1-3	Fixture Finish/Type	White Plastic frame+Plastic cover
1-4	Fixture Wattage	15W
1-5	Rated Average Life (hours) L70	50,000
1-6	LED Type	SMD
1-7	Reliable Operating Temperature	-4F to 113F



2 Photometric Characteristics

2-1	Initial Lumens	1050
2-2	Initial Lumens per Watt	70
2-3	Color Temperature	3000K
2-4	Color Rendering Index (CRI)	≥80



3 Electrical Characteristics

3-1	Input Line Voltage/Frequency	120V, 60 Hz	3-4	Power Factor	>0.9
3-2	Lamp rated Wattage	15W	3-5	Dimming Type	Triac(10-100%)
3-3	Total Harmonic Distortion	<20%			

4 Dimensional Characteristics

4-1	Width (mm)	300
4-2	Height	96.5

5 Product Information

5-1	Primary Application	Residential/Hospitality
5-2	Warranty	5 Years from date of purchase
5-3	Certified	ETL/ES/LM79
5-4	RoHS Compliant	Yes
5-5	Environment	Suitable for Damp Location/Indoor Use

6 Packing Details

6-1	Box size (mm)	560 x 345 x 350	6-3	Net Weight (Kg)	TBA
6-2	Qty /Box	8 pcs	6-4	Gross Weight (Kg)	TBA

01/2017© Overdrive

For more information visit www.overdrive-lighting.com.com

*Note: This document is property of "OVERDRIVE Electronics Pvt. Ltd" and should not be copied or distributed without written permission.
This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.*




LED 15W 12" Flush Mount Ceiling

Item # 818
L15FM12PLDIM/30K

1 FIXTURE SPECIFICATION

1-1	Fixture Type	LED Flush Mount
1-2	Dimmable (Y/N)	YES(Triac)
1-3	Lamp Finish/Type	White Plastic frame+Plastic cover
1-4	Lamp Wattage	15W
1-5	Rated Average Life (hours) L70	50,000
1-6	LED Type	SMD
1-7	Reliable Operating Temperature	-4F to 113F



2 Photometric Characteristics

2-1	Initial Lumens	1050
2-2	Initial Lumens per Watt	70
2-3	Color Temperature	3000K
2-4	Color Rendering Index (CRI)	≥80



3 Electrical Characteristics

3-1	Input Line Voltage/Frequency	120V, 60 Hz	3-4	Power Factor	>0.9
3-2	Lamp rated Wattage	15W	3-5	Dimming Type	Triac(10-100%)
3-3	Total Harmonic Distortion	<20%			

4 Dimensional Characteristics

4-1	Width (mm)	300
4-2	Height	96.5

5 Product Information

5-1	Primary Application	Residential/Hospitality
5-2	Limited Warranty	5 Years from date of purchase
5-3	Certified	ETL/ES/LM79
5-4	RoHS Compliant	Yes
5-5	Environment	Suitable for Damp Location/Indoor Use

6 PACKING DETAILS

6-1	Box size (mm)	560 x 345 x 350	6-3	Net Weight (Kg)	TBA
6-2	Qty /Box	8 pcs	6-4	Gross Weight (Kg)	TBA

01/2017© Overdrive

For more information visit www.overdrive-lighting.com

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.