




		LED 22W 14" Flush Mount Ceiling		Item # 821	
				L22FM14PLDIM/40K	
1 FIXTURE SPECIFICATION					
1-1	Fixture Type	LED Flush Mount Ceiling			
1-2	Dimmable (Y/N)	YES (Triac)			
1-3	Fixture Finish/Type	White Plastic frame+Plastic cover			
1-4	Fixture Wattage	22W			
1-5	Rated Average Life (hours) L70	50,000			
1-6	LED Type	SMD			
1-7	Reliable Operating Temperature	-4F to 113F			
2 Photometric Characteristics					
2-1	Initial Lumens	1600		 	
2-2	Initial Lumens per Watt	73			
2-3	Color Temperature	4000K			
2-4	Color Rendering Index (CRI)	≥80			
3 Electrical Characteristics					
3-1	Input Line Voltage/Frequency	120V ,60 Hz	3-4	Power Factor	>0.9
3-2	Lamp rated Wattage	22W	3-5	Dimming Type	Triac(10-100%)
3-3	Total Harmonic Distortion	<20%			
4 Dimensional Characteristics					
4-1	Width (mm)	355.6			
4-2	Height (mm)	96.5			
5 Product Information					
5-1	Primary Application	Residential/Hospitality			
5-2	Limited Warranty	5 Years from date of purchase			
5-3	Certified	ETL/ES/LM79			
5-4	RoHS Compliant	Yes			
5-5	Environment	Suitable for Damp Location/Indoor Use			
6 Packing Details					
6-1	Box size (mm)	560 x 415 x 420	6-3	Net Weight (Kg)	TBA
6-2	Qty /Box	8 pcs	6-4	Gross Weight (Kg)	TBA
01/2017© Overdrive For more information visit www.overdrive-lighting.com					
Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.					

		Led Flush Mount Ceiling Dimmable		Item # 820	
		22W 3000K 14 Inch		L22FM14PLDIM/30K	
1 FIXTURE SPECIFICATION					
1-1	Fixture Type	LED Flush Mount Ceiling			
1-2	Dimmable (Y/N)	YES			
1-3	Fixture Finish/Type	White Plastic frame+Plastic cover			
1-4	Fixture Wattage	22W			
1-5	Rated Average Life (hours) L70	50,000			
1-6	LED Type	SMD			
1-7	Reliable Operating Temperature	-4F to 113F			
2 Photometric Characteristics					
2-1	Initial Lumens	1600		 	
2-2	Initial Lumens per Watt	73			
2-3	Color Temperature	3000K			
2-4	Color Rendering Index (CRI)	≥80			
3 Electrical Characteristics					
3-1	Input Line Voltage/Frequency	120V , 50/60 Hz		3-4	Power Factor >0.9
3-2	Lamp rated Wattage	22W		3-5	Dimming Type 10-100%
3-3	Total Harmonic Distortion	<20%			
4 Dimensional Characteristics					
4-1	Width (mm)	355.6			
4-2	Height	96.5			
5 Product Information					
5-1	Primary Application	Residential/Hospitality			
5-2	Warranty	5 Years from date of purchase			
5-3	Certified	ETL/ES/LM79			
5-4	RoHS Compliant	Yes			
6 Packing Details					
6-1	Box size (mm)	560 x 415 x 420	6-3	Net Weight (Kg)	TBA
6-2	Qty /Box	8 pcs	6-4	Gross Weight (Kg)	TBA
01/2017© Overdrive					
For more information visit www.overdrive-lighting.com.com					
Note: This document is property of "OVERDRIVE Electronics Pvt. Ltd" and should not be copied or distributed without written permission.					
This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.					