

## LED 320W Linear 4' High Bay

Item # 804

L320HBL46DIM/50K

| <b>1 FIXTURE SPECIFICATION</b>      |   | _            |   |  |
|-------------------------------------|---|--------------|---|--|
| 1-1 Fixture Type                    | LED Linear High Bay                     |              |   |  |
| 1-2 Dimmable (Y/N)                  | YES (0-10V)                             |              |   |  |
| 1-3 Fixture Finish/Type             | White Painted Steel Body                |              |   |  |
| 1-4 Fixture Wattage                 | 320W                                    |              |   |  |
| 1-5 Rated Average Life (hours) L7   | 0 50,000                                |              | - Arrent Children and Children |  |
| 1-6 LED Type                        | SMD                                     |              |   |  |
| 1-7 Reliable Operating Temperatu    | re -4F to 1131                          | -            |   |  |
| 2 Photometric Characterist          | tics                                    |              | SUCPT   |  |
| 2-1 Initial Lumens                  | 39000                                   |              | VALES.  | LISTED   |
| 2-2 Initial Lumens per Watt         | 122                                     |              | Not all products are qualifie<br>QPL. To view DLC qualified p<br>consult the DLC qualified p<br>www.designlights.c  | roducts list at                                |
| 2-3 Color Temperature               | 5000K                                   |              |   |  |
| 2-4 Color Rendering Index (CRI)     | ≥80                                     |              |   |  |
| <b>3</b> Electrical Characteristics |   |              |   |  |
| 3-1 Input Line Voltage/Frequency    | 120V - 277V                             | , 60 Hz      | 3-4 Power Factor  | >0.9   |
| 3-2 Lamp rated Wattage              | 320W                                    |              | 3-5 Dimming Typ   | e (0-10V)10-100                                |
| 3-3 Total Harmonic Distortion       | <20%                                    |              |   |  |
| 4 Dimensional Characteris           | stics                                   | _            |   |  |
|                                     |   |              | <u>-</u><br>•©⊙•IIIIII IIIII IIIII IIIII  | .1156<br>• • • • • • • • • • • • • • • • • • • |
|                                     |   |              | L X B X H (mm)  | 1166 x 440 x 92                                |
| 5 Product Information               |   |              |   |  |
| 5-1 Primary Application             | Industrial/Ware Hou                     | ise/Manu     | facturing Facility  |  |
| 5-2 Limited Warranty                | 5 Years from date of purchase           |              |   |  |
| 5-3 Certified                       | UL/DLC/LM79                             |              |   |  |
| 5-4 RoHS Compliant                  | Yes                                     |              |   |  |
| 5-5 Environment                     | Suitable for Damp Location / Indoor Use |              |   |  |
| 6 Packing Details                   | 1                                       | ,            |   |  |
| 6-1 Box size (mm)                   | 1195 x 449 x 98                         | 6-3          | Net Weight (Kg)   | 9.6  |
| 6-2 Qty /Box                        | 1 pcs                                   | 6-4          | Gross Weight (Kg)   | 11   |
|                                     | nore information visit ww               |              |   |  |
| Note: This data sheet is not c      | ontrolled copy & is subject to ci       | hange withou | t notice. Standard Tolerances apply   | on data given above.                           |