| Överdrive [®] | I ED 32W 5000k | (A! Strin Kit | ltem # 808 | |
|------------------------------------|--------------------------------|---------------------------------------|--|----------------|
| LED by Innovation | LED 32W 5000K 4' Strip Kit | | L32STK4DIM/50K | |
| 1 FIXTURE SPECIFICATION | | | | |
| 1-1 Fixture Type | LED Strip | | | |
| 1-2 Dimmable (Y/N) | YES (0-10V) | | | |
| 1-3 Lamp Finish/Type | White Painted Steel | Body | | . 0 |
| 1-4 Lamp Wattage | 32W | | 2 | |
| 1-5 Rated Average Life (hours) L70 | 50,000 | | | |
| 1-6 LED Type | SMD | C | | |
| 1-7 Reliable Operating Temperature | -4F to 113F | | | |
| 2 Photometric Characteristics | | l l l l l l l l l l l l l l l l l l l | CUL us | |
| 2-1 Initial Lumens | 3840 | _Not all prod | LISTED | |
| 2-2 Initial Lumens per Watt | 120 | OPL. To view consult the www | DLC qualified products, Please DLC qualified products list at w.designlights.org/qpl | |
| 2-3 Color Temperature | 5000K | | | |
| 2-4 Color Rendering Index (CRI) | ≥80 | | | |
| 3 Electrical Characteristics | | | | |
| 3-1 Input Line Voltage/Frequency | 120V - 277V, 60 Hz | 3-4 Power Factor | | >0.9 |
| 3-2 Lamp rated Wattage | 32W | 3-5 Dimming Ty | ре | (0-10V)10-100% |
| 3-3 Total Harmonic Distortion | <20% | | | |
| 4 Dimensional Characteristics | 5 | | | |
| | 1228 | | 1 | <u>60</u> |
| | | | | |
| | · · · · · · · · · | ۰ ۰ ۰ | • • • | |
| | • • • • • | • • • | | 4 |
| | | | | |
| | | L X B X H (mm) | 1228 x 146.3 x 60 | |
| 5 Product Information | | | | |
| | trofit Application in Industri | al /Commercial | | |
| | fears from date of purchase | | | |
| | L/DLC/LM79 | | | |
| 5-4 RoHS Compliant Ye | | | | |
| - | itable for Damp Location/In | door Use | | |
| 6 Packing Details | | | | |
| 6-1 Box size (mm) 120 | 65 x 182 x 158 6-3 | Net Weight (Kg) | 2.45 | |
| 6-2 Qty /Box 2 p | DCS 6-4 | Gross Weight (Kg) | 6.4 | |
| | | | | |