



# 6W LED Globe Dimmable - 3000K

Item # 606

L6G25DIM/30K

## 1 LAMP SPECIFICATION

1-1	Lamp Type	LED Globe
1-2	Dimmable (Y/N)	YES
1-3	Base	E26 (Medium Base)
1-4	Lamp Finish/Type	G25
1-5	Lamp Wattage	6W
1-6	Wattage Comparison (FC on Floor)	40W Incand.
1-7	Rated Average Life (hours) L70	25,000
1-8	Reliable Operating Temperature	-4F to 113F



## 2 Photometric Characteristics

2-1	Initial Lumens	470
2-2	Centre Beam Candle Power (Cd)	NA
2-3	Beam Angle (50%) in Degree	175
2-4	Initial Lumens per Watt	78
2-5	Color Temperature	3000K
2-6	Color Rendering Index (CRI)	80

## 3 Electrical Characteristics

3-1	Input Line Voltage/Frequency	120V 60 Hz	3-2	Power Factor	0.96
3-3	Lamp rated Wattage	6W	3-4	Input Line Current	55mA
3-5	Total Harmonic Distortion	20%	3-6	Dimming Range	Full

## 4 Dimensional Characteristics

4-1	Nominal Length (Inches/mm)	4.25" / 108 mm	4-2	Diameter	3.15" / 80 mm
-----	----------------------------	----------------	-----	----------	---------------

## 5 Product Information

5-1	Description	6W LED Globe Dimmable - 3000K			
5-2	Primary Application	Household Use, Office, Agriculture & Commercial			
5-3	Warranty	5 Years from date of purchase			
5-4	TCLP Compliant	YES	5-6	RoHS Compliant	YES
5-5	Energy Star (Y/N)	YES	5-7	UL / FCC	YES

## 6 PACKING DETAILS

6-1	Color Box Size (Inches)	1x1	3.2 x 3.2 x 4.6	6-2	Inner Carton Size (Inches)	NA
6-3	Master Carton Size (Inches)	1x12	13.82 x 10.43 x 5.94	6-4	Gross Weight / Net Weight ( lbs )	3.59 / 2.01

01/2017© Overdrive For more information visit [www.overdrive-lighting.com](http://www.overdrive-lighting.com)

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.