

## 6.5W LED 90CRI PAR20 Flood Dimmable - 5000K

Item # 638

L6HPAR20DIM/FL/50K

_	I					
1	LAMP SPECIFICATION					
1-1	Lamp Type		LED 90CRI PAR20			
1-2	Dimmable (Y/N)		YES			CONTRACT OF THE PARTY OF THE PA
1-3	Base		E26			
1-4	Lamp Finish/Type		PAR20		The same of the sa	and the second
1-5	Lamp Wattage		6.5W			
1-6	Wattage Comparison (FC on Floor)	)	50W Incand			
1-7	Rated Average Life (hours) L70		35,000			
1-8	Reliable Operating Temperature		-4F to 113F			
2	Photometric Characteristics					
2-1	Initial Lumens		495			
2-2	Centre Beam Candle Power (Cd)		680			
2-3	Beam Angle (50% I Max) in Degree		40			
2-4	Beam Angle (10% I Max) in Degree		N/A			_
2-5	Initial Lumens per Watt		76		c(UL)us	Roks
2-6	Color Temperature		5000K			<u>Compliant</u>
2.7	Color Rendering Index (CRI)		90			
3	Electrical Characteristics					
3-1	Input Line Voltage/Frequency		120V 60 Hz	3-2	Power Factor	0.91
3-3	Lamp rated Wattage		6.5W	3-4	Input Line Current	55mA
3-5	Total Harmonic Distortion		34%	3-6	Dimming Range in %	Full
4	Dimensional Characteristics					
4-1	Nominal Length (Inches/mm)		3.23"/82mm	4-2	Diameter	2.48"/63mm
5	Product Information					
5-1	Description 6.5W LED 90CRI PAR20 Dimmable FLOOD - 5000K					
5-2	Primary Application	Household Use, Office & Commercial- Wet Location				
5-3	Warranty	5 Years from o	late of purchase			
5-4	TCLP Compliant	YES		5-6	RoHS Compliant	YES
5-5	Energy Star or LM79 (Y/N)	NO		5-8	UL / FCC	YES
6	PACKING DETAILS					
6-1	Color Box Size (Inches) 1x1	2.6 X 2.6 X 3.6		6-2	Inner Carton Size (cm) 1x12	N/A
6-3	Master Carton Size (Inches) 1x12	11.54 X 8.78 X 4.92		6-4	Gross Weight / Net Weight ( lbs )	3.24 / 2.03
01/2017© Overdrive For more information visit www.overdrive-lighting.com						
Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.						