

10W LED 90 CRI R30 Reflector Dimmable - 2700K

Item # 570

L10HR30DIM/27K

1	LAMP SPECIFICATION						
1-1	Lamp Type LED R30 Bulb - Opal Cover						
1-2	Dimmable (Y/N)		YES				
1-3	Base		E26 (Medium Base)				
1-4	Lamp Finish/Type		BR30 Shape				
1-5	Lamp Wattage		10W				
1-6	Wattage Comparison (FC on Floor)		65W BR30 Incand				
1-7	Rated Average Life (hours) L70		25000				
1-8	LED Type		Seoul- SMD (LM80)				
1-9	Reliable Operating Temperature		-4F to 113F				
2	Photometric Characteristics						
2-1	Initial Lumens	670					
2-2	Centre Beam Candle Power (Cd)	220					
2-3	Beam Angle (50%) in Degree		108				
2-4	Initial Lumens per Watt		67		C (AL)	US Gomp	iant
2-5	Color Temperature		2700K				
2-6	Color Rendering Index (CRI)		90				
3	Electrical Characteristics						
3-1	Input Line Voltage/Frequency		120V 60 Hz	3-2	Power Factor		0.99
3-3	Lamp rated Wattage		10W	3-4	Input Line Current		90 mA
3-5	Total Harmonic Distortion		20%	3-6	Dimming Range in %		Full
4	Dimensional Characteristics						
	Nominal Length (Inches/mm)	Ţ.	5.2" / 131 mm	4-2	Diameter		3.74" / 95 mm
5	Product Information						
5-1	Description 10W LED 90 CRI BR30 Reflector Dimmable, Warm White, Medium Base						
5-2	rimary Application Household Use, Office, Agriculture & Commercial						
5-3	Warranty	5 Years from o	late of purchase				
5-4	TCLP Compliant	YES		5-6	RoHS Compliant		YES
5-5	Energy Star (Y/N)	YES		5-7	UL / FCC		YES
6	PACKING DETAILS						
6-1	Color Box Size (Inches) 1x1	3.9 X 3.9 X 4.5		6-2	Inner Carton Size (Inc	ches)	NA
6-3	Master Carton Size (Inches) 1x12	16.46 X 12.44 X	7.09	6-4	Gross Weight / Net V	Veight (lbs)	7.34 / 4.63
01/20	017© Overdrive For more information	visit www.overdr	ive-lighting.com				

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.