

## 10W LED A Bulb Dimmable -

3000K

## ltem # 611

## L10A19DIM/30K

| 1     | LAMP SPECIFICATION   |   |                                  | _   |                                   |                     |  |
|-------|--|---|----------------------------------|-----|-----------------------------------|---------------------|--|
| 1-1   | Lamp Type  | LED A Bulb Dimmable                             |                                  |     |                                   |                     |  |
| 1-2   | Dimmable (Y/N)   |   | YES                              |     |                                   |                     |  |
| 1-3   | Base   |   | E26 (Medium Base)                |     |                                   | 100                 |  |
| 1-4   | Lamp Finish/Type   |   | A19 Shape                        |     |                                   |                     |  |
| 1-5   | Lamp Wattage   |   | 10W                              |     |                                   |                     |  |
| 1-6   | Wattage Comparison (FC on Floor)   |   | 100W Incand (based on Floor Lux) |     |                                   |                     |  |
| 1-7   | Rated Average Life (hours) L70   |   | 40,000                           |     |                                   |                     |  |
| 1-8   | Reliable Operating Temperature   |   | -4F to 113F                      |     |                                   |                     |  |
| 2     | Photometric Characteristics  |   |                                  |     |                                   |                     |  |
| 2-1   | Initial Lumens   | 930   |                                  |     | -                                 |                     |  |
| 2-2   | Centre Beam Candle Power (Cd)  |   | 230                              |     |                                   |                     |  |
| 2-3   | Beam Angle (50% I Max) in Degree   |   | 125                              |     |                                   |                     |  |
| 2-4   | Beam Angle (10% I Max) in Degree   |   | 205                              |     |                                   | 2045                |  |
| 2-5   | Initial Lumens per Watt  |   | 93                               |     |                                   | Compliant           |  |
| 2-6   | Color Temperature  |   | 3000K                            |     |                                   |                     |  |
| 2.7   | Color Rendering Index (CRI)  |   | 82                               |     |                                   |                     |  |
| 3     | Electrical Characteristics   |   |                                  |     |                                   |                     |  |
| 3-1   | Input Line Voltage/Frequency   |   | 120V 60 Hz                       | 3-2 | Power Factor                      | 0.94                |  |
| 3-3   | Lamp rated Wattage   |   | 10W                              | 3-4 | Input Line Current                | 85 mA               |  |
| 3-5   | Total Harmonic Distortion  |   | 30%                              | 3-6 | Dimming Range in %                | Full                |  |
| 4     | Dimensional Characteristics  |   |                                  |     |                                   |                     |  |
| 4-1   | Nominal Length (Inches/mm)   | 2   | 4.3" / 108 mm                    | 4-2 | Diameter                          | 2.3" / 58 mm        |  |
| 5     | Product Information  |   |                                  |     |                                   |                     |  |
| 5-1   | Description  | cription 10W LED A Bulb Dimmable -3000K         |                                  |     |                                   |                     |  |
| 5-2   | Primary Application  | Household Use, Office, Agriculture & Commercial |                                  |     |                                   |                     |  |
| 5-3   | Warranty   | 5 Years from date of purchase                   |                                  |     |                                   |                     |  |
| 5-4   | TCLP Compliant YES   |   |                                  | 5-6 | RoHS Compliant                    | YES                 |  |
| 5-5   | Energy Star or LM79(Y/N)   | LM79  |                                  | 5-8 | UL / FCC                          | YES                 |  |
| 6     | PACKING DETAILS  |   |                                  |     |                                   |                     |  |
| 6-1   | Color Box Size (Inches) 1x1  | 2.4 x 2.4 x 4.9                                 |                                  | 6-2 | Inner Carton Size (Inches) 1x12   | 10.63 x 7.95 x 5.71 |  |
| 6-3   | Master Carton Size (Inches) 1x48 16.02 x 10.83 x 2   |   | 12.13                            | 6-4 | Gross Weight / Net Weight ( lbs ) | 14.17 / 8.88        |  |
|       | 017© Overdrive For more information  |   | 8 8                              |     |                                   |                     |  |
| Note: | Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above. |   |                                  |     |                                   |                     |  |