

10W LED A Bulb Dimmable - 5000K

Item # 612

L10A19DIM/50K

					J, JOK	
1	LAMP SPECIFICATION					
1-1	Lamp Type	LED A Bulb Dimmable				
1-2	Dimmable (Y/N)	YES				
1-3	Base	E26 (Medium Base)				
1-4	Lamp Finish/Type	A19 Shape		No. of the last of		
1-5	Lamp Wattage	10W				
1-6	Wattage Comparison (FC on Floo	100W Incand (based on Floor Lux)				
1-7	Rated Average Life (hours) L70	40,000	40,000			
1-8	LED Type	10 nos. x 0.84W	10 nos. x 0.84W			
1-9	Reliable Operating Temperature	-4F to 113F				
2	Photometric Characteristics					
2-1	Initial Lumens	1000				
2-2	Centre Beam Candle Power (Cd)	260				
2-3	Beam Angle (50% I Max) in Degre	e 125				
2-4	Beam Angle (10% I Max) in Degre	e 205		الله الله الله الله الله الله الله الله		
2-5	Initial Lumens per Watt	100		Gom	pliant	
2-6	Color Temperature	5000K				
2.7	Color Rendering Index (CRI)	82				
3	Electrical Characteristics					
3-1	Input Line Voltage/Frequency	120V 60 Hz	3-2	Power Factor	0.94	
3-3	Lamp rated Wattage	10W	3-4	Input Line Current	85 mA	
3-5	Total Harmonic Distortion	30%	3-6	Dimming Range in %	Full	
4	Dimensional Characteristic	5				
4-1	Nominal Length (Inches/mm)	4.3" / 108 mm	4-2	Diameter	2.3" / 58 mm	
5	Product Information					
5-1	Description	10W LED A Bulb Dimmable - 5000K				
5-2	Primary Application	Household Use, Office, Agriculture & Commercial				
5-3	Warranty	5 Years from date of purchase				
5-4	TCLP Compliant	YES	5-6	RoHS Compliant	YES	
5-5	Energy Star or LM79 (Y/N)	LM79	5-8	UL / FCC	YES	
6	PACKING DETAILS					
6-1	Color Box Size (Inches) 1x1	2.4 x 2.4 x 4.9	6-2	Inner Carton Size (Inches) 1x12	10.63 x 7.95 x 5.71	
6-3	Master Carton Size (Inches) 1x4	16.02 x 10.83 x 12.13	6-4	Gross Weight / Net Weight (lbs)	14.17 / 8.88	
01/2017© Overdrive For more information visit www.overdrive-lighting.com						

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.