

LED 14W T8 4FT- Ballast compatible SSC - 4000K

Item # 614

L14T84FTIS/40K

	-						
1	LAMP SPECIFICATION						
1-1	Lamp Type	LED T8 IS BALLAST COMPATIBLE					
1-2	Dimmable (Y/N)	nmable (Y/N) No			11/1		
1-3	Base	G13	G13				
1-4	Lamp Finish/Type	Glass - T8	Glass - T8				
1-5	Lamp Wattage	14W	14W				
1-6	Wattage Comparison (FC on Floor)	up to 32W	up to 32W				
1-7	Rated Average Life (hours) L70	50,000	50,000				
1-8	Reliable Operating Temperature	-4F to 113	-4F to 113F				
2	Photometric Characteristics						
2-1	Initial Lumens	1800					
2-2	Centre Beam Candle Power (Cd)	260			· ·		
2-3	Beam Angle (50% I Max) in Degree	230	230				
2-4	Initial Lumens per Watt	129					
2-5	Color Temperature	4000K			O E OS Complian		
2-6	Color Rendering Index (CRI)	82	82				
3	Electrical Characteristics						
3-1	Input Line Voltage/Frequency	IS Ballast	120 - 277V input	3-2	Power Factor	0.95	
3-3	Lamp rated Wattage	14W	3	3-4	Input Line Current	168	
3-5	Total Harmonic Distortion	20%	3	3-6	Dimming Range in %		
4	Dimensional Characteristics						
4-1	Nominal Length (Inches/mm)	48" / 1213	3 mm	1-2	Diameter	1.02" / 26 mm	
5	Product Information						
5-1	Description LED 14W T8 4FT- Ballast compatible - 4000K						
5-2	Primary Application	Household Use, Office, Agriculture & Commercial					
5-3	Warranty	5 Years from date of purchase					
5-4	TCLP Compliant	YES	ŗ	5-6	RoHS Compliant	YES	
5-5	Energy Star or LM79 (Y/N)	DLC		5-8	UL / FCC	YES	
6	PACKING DETAILS						
6-1	Color Box Size (Inches) 1x1	48 x 1.2 x 1.2		6-2	Inner Carton Size (Inches)	NA	
6-3	Master Carton Size (Inches) 1x25	49.61 x 8.27 x 8.66		6-4	Gross Weight / Net Weight (lbs)	15.43 / 11.02	
01/2017© Overdrive For more information visit www.overdrive-lighting.com							
Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.							