

10.5W LED 90CRI PAR30 LONG NECK Dimmable FLOOD - 3000K

Item # 632

L10HPAR30LNDIM/FL/30K

1	LAMP SPECIFICATION			_			
1-1	Lamp Type	LED 90CRI PAR30 LONG NECK					
1-2	Dimmable (Y/N)		YES				
1-3	Base		E26		Construction of the second	MUIII	
1-4	Lamp Finish/Type		PAR30				
1-5	Lamp Wattage		10.5W			Innus	
1-6	Wattage Comparison (FC on Floor)		75W Incand (based on Floor Lux)				
1-7	Rated Average Life (hours) L70		25,000				
1-8	LED Type		9 X 0.96W SMD.				
1-9	Reliable Operating Temperature		-4F to 113F		Øverdrive		
2	Photometric Characteristics						
2-1	Initial Lumens		720				
2-2	Centre Beam Candle Power (Cd)		1440		ANN -		
2-3	Beam Angle (50% I Max) in Degree		40(Flood)				
2-4	Beam Angle (10% I Max) in Degree		N/A				
2-5	Initial Lumens per Watt		69 COMPLIANT CONDIANT			Compliant	
2-6	Color Temperature		3000K				
2.7	Color Rendering Index (CRI)		90				
3	Electrical Characteristics						
3-1	Input Line Voltage/Frequency		120V 60 Hz	3-2	Power Factor	0.96	
3-3	Lamp rated Wattage		10.5W	3-4	Input Line Current	90 mA	
3-5	Total Harmonic Distortion		18%	3-6	Dimming Range in %	Full	
4	Dimensional Characteristics						
4-1	Nominal Length (Inches/mm)		4.57" / 116 mm	4-2	Diameter	3.74" / 95 mm	
5	Product Information						
5-1	Description	10.5W LED 90CRI PAR30 LONG NECK Dimmable FLOOD - 3000K					
5-2	Primary Application	Household Use, Office & Commercial- Wet Location					
5-3			m date of purchase				
5-4	TCLP Compliant YES			5-6	RoHS Compliant	YES	
5-5	Energy Star or LM79 (Y/N) ES			5-8	UL / FCC	YES	
6	PACKING DETAILS						
6-1	Color Box Size (Inches) 1x1 3.9 x 3.9 x 4.		9	6-2	Inner Carton Size (Inches) 1x12	N/A	
6-3	Master Carton Size (Inches) 1x12 16.65 x 12.60) x 6.22	6-4	Gross Weight / Net Weight (lbs)	7.07 / 4.76	
	01/2017© Overdrive For more information visit www.overdrive-lighting.com						
Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.							