

16.5W LED 90CRI PAR38 Dimmable FLOOD - 5000K

Item # 634

L16HPAR38DIM/FL/50K

1-1 LAMP SPECIFICATION 1-1 Lamp Type	
1-2 Dimmable (Y/N) 1-3 Base E26 1-4 Lamp Finish/Type PAR38 1-5 Lamp Wattage 16.5W 1-6 Wattage Comparison (FC on Floor) 90W Incand (based on Floor Lux) 1-7 Rated Average Life (hours) L70 35,000 1-8 Reliable Operating Temperature -4F to 113F Photometric Characteristics 2-1 Initial Lumens 1250 2-2 Centre Beam Candle Power (Cd) 2300 1-3 Beam Angle (50% I Max) in Degree 40 1-4 Beam Angle (10% I Max) in Degree N/A 1-5 Color Temperature 5000K 1-7 Color Rendering Index (CRI) 90 1-8 Beam Angle (10% I Max) in Degree N/A 1-9 Door Rendering Index (CRI) 90 1-9 Door Reliable Operations 10 Door Lux) 1-1 Door Lux 1-1 Door Lux 1-1 Door Lux 1-1 Door Lux 1-2 Door L	
Base E26 Lamp Finish/Type PAR38 1-5 Lamp Wattage 16.5W Wattage Comparison (FC on Floor) 90W Incand (based on Floor Lux) Rated Average Life (hours) L70 35,000 Reliable Operating Temperature -4F to 113F Photometric Characteristics Initial Lumens 1250 Centre Beam Candle Power (Cd) 2300 Beam Angle (50% I Max) in Degree 40 Beam Angle (10% I Max) in Degree N/A Initial Lumens per Watt 76 Color Temperature 5000K Color Rendering Index (CRI) 90 Blectrical Characteristics	
Lamp Finish/Type	
Lamp Wattage 16.5W Wattage Comparison (FC on Floor) Rated Average Life (hours) L70 Reliable Operating Temperature Photometric Characteristics Initial Lumens Centre Beam Candle Power (Cd) Beam Angle (50% I Max) in Degree Beam Angle (10% I Max) in Degree N/A Photometric Characteristics Initial Lumens Color Temperature 5000K Color Rendering Index (CRI) Blectrical Characteristics	
1-6 Wattage Comparison (FC on Floor) 1-7 Rated Average Life (hours) L70 1-8 Reliable Operating Temperature 2 Photometric Characteristics 2-1 Initial Lumens 1250 2-2 Centre Beam Candle Power (Cd) 2-3 Beam Angle (50% I Max) in Degree 40 2-4 Beam Angle (10% I Max) in Degree N/A 2-5 Initial Lumens per Watt 76 2-6 Color Temperature 5000K 2.7 Color Rendering Index (CRI) 90 Electrical Characteristics	
1-7 Rated Average Life (hours) L70 1-8 Reliable Operating Temperature -4F to 113F Photometric Characteristics 2-1 Initial Lumens 1250 2-2 Centre Beam Candle Power (Cd) 2-3 Beam Angle (50% I Max) in Degree 40 2-4 Beam Angle (10% I Max) in Degree N/A 2-5 Initial Lumens per Watt 76 2-6 Color Temperature 5000K 2-7 Color Rendering Index (CRI) 90 Electrical Characteristics	
1-8 Reliable Operating Temperature -4F to 113F 2 Photometric Characteristics 2-1 Initial Lumens 1250 2-2 Centre Beam Candle Power (Cd) 2300 2-3 Beam Angle (50% I Max) in Degree 40 2-4 Beam Angle (10% I Max) in Degree N/A 2-5 Initial Lumens per Watt 76 2-6 Color Temperature 5000K 2-7 Color Rendering Index (CRI) 90 3 Electrical Characteristics	
Photometric Characteristics 2-1 Initial Lumens 2-2 Centre Beam Candle Power (Cd) 2-3 Beam Angle (50% I Max) in Degree 40 2-4 Beam Angle (10% I Max) in Degree N/A 2-5 Initial Lumens per Watt 76 Color Temperature 5000K 2.7 Color Rendering Index (CRI) 90 Electrical Characteristics	
Initial Lumens 2-1 Initial Lumens 1250 2-2 Centre Beam Candle Power (Cd) 2300 Beam Angle (50% I Max) in Degree 40 2-4 Beam Angle (10% I Max) in Degree N/A 2-5 Initial Lumens per Watt 76 2-6 Color Temperature 5000K 2.7 Color Rendering Index (CRI) 90 Electrical Characteristics	
2-2 Centre Beam Candle Power (Cd) 2-3 Beam Angle (50% I Max) in Degree 40 2-4 Beam Angle (10% I Max) in Degree N/A 2-5 Initial Lumens per Watt 76 2-6 Color Temperature 5000K 2.7 Color Rendering Index (CRI) 90 Electrical Characteristics	
2-3 Beam Angle (50% I Max) in Degree 40 2-4 Beam Angle (10% I Max) in Degree N/A 2-5 Initial Lumens per Watt 76 2-6 Color Temperature 5000K 2.7 Color Rendering Index (CRI) 90 Electrical Characteristics	
2-4 Beam Angle (10% I Max) in Degree N/A 2-5 Initial Lumens per Watt 76 2-6 Color Temperature 5000K 2.7 Color Rendering Index (CRI) 90 3 Electrical Characteristics	
2-5 Initial Lumens per Watt 76 2-6 Color Temperature 5000K 2.7 Color Rendering Index (CRI) 90 Electrical Characteristics	
2-6 Color Temperature 5000K 2.7 Color Rendering Index (CRI) 90 Electrical Characteristics	
2.7 Color Rendering Index (CRI) 90 3 Electrical Characteristics	
3 Electrical Characteristics	
3-1 Input Line Voltage/Frequency 120V 60 Hz 3-2 Power Factor 0.96	
3-3 Lamp rated Wattage 16.5W 3-4 Input Line Current 140 mA	
3-5 Total Harmonic Distortion 15% 3-6 Dimming Range in % Full	
4 Dimensional Characteristics	
4-1 Nominal Length (Inches/mm) 5.16"/131mm 4-2 Diameter 4.76"/121m	ım
5 Product Information	
5-1 Description 16.5W LED 90CRI PAR38 Dimmable FLOOD - 5000K	
5-2 Primary Application Household Use, Office & Commercial- Wet Location	
5-3 Warranty 5 Years from date of purchase	
5-4 TCLP Compliant YES 5-6 RoHS Compliant YES	
5-5 Energy Star or LM79 (Y/N) No 5-8 UL / FCC YES	
6 PACKING DETAILS	
6-1 Color Box Size (Inches) 1x1 4.9 x 4.9 x 5.5 6-2 Inner Carton Size (Inches) 1x12 N/A	
6-3 Master Carton Size (Inches) 1x12 20.75 x 15.67 x 6.81 6-4 Gross Weight / Net weight (lbs) 10.51 / 7.03	
01/2017© Overdrive For more information visit www.overdrive-lighting.com	

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.