



**14W LED EH80 Utility Luminaire  
Hard Wire - 5000K**

**Item # 652**

**L14EH80-W/HB/50K**

**1 LAMP SPECIFICATION**

1-1	Lamp Type	EH80
1-2	Dimmable (Y/N)	NO
1-3	Base	With Hard Wire Connector
1-4	Lamp Finish/Type	EH80 Utility Light
1-5	Lamp Wattage	14W
1-6	Wattage Comparison (FC on Floor)	140W Incand/32W CFL
1-7	Rated Average Life (hours) L70	50,000
1-8	Reliable Operating Temperature	-4F to 113F



**2 Photometric Characteristics**

2-1	Initial Lumens	1470
2-2	Centre Beam Candle Power (Cd)	260
2-3	Beam Angle (50% I Max) in Degree	165
2-4	Beam Angle (10% I Max) in Degree	275
2-5	Initial Lumens per Watt	100
2-6	Color Temperature	5000K
2-7	Color Rendering Index (CRI)	80



**3 Electrical Characteristics**

3-1	Input Line Voltage/Frequency	120V 60 Hz	3-2	Power Factor	0.98
3-3	Lamp rated Wattage	14W	3-4	Input Line Current	130mA
3-5	Total Harmonic Distortion	<20%	3-6	Dimming Range in %	No

**4 Dimensional Characteristics**

4-1	Nominal Length (Inches/mm)	6.10" / 155 mm	4-2	Diameter	4.13" / 105 mm
-----	----------------------------	----------------	-----	----------	----------------

**5 Product Information**

5-1	Description	14W LED EH80 Utility Luminaire Hard Wire Connector - 5000K			
5-2	Primary Application	Commercial, Industrial, Agriculture, Refrigerator, Tunnel, Walk Way			
5-3	Warranty	5 Years from date of purchase			
5-4	TCLP Compliant	YES	5-6	RoHS Compliant	YES
5-5	Energy Star or LM79 (Y/N)	TBA	5-8	ETL - Wet Location	YES

**6 PACKING DETAILS**

6-1	Color Box Size (Inches)	1x1	4.6 x 4.6 x 6.7	6-2	Inner Carton Size (Inches)	N/A
6-3	Master Carton Size (Inches)	1x12	19.09 x 14.37 x 7.48	6-4	Gross Weight / Net Weight ( lbs )	12.12 / 7.93