

20W LED H80 Lamp - 2700K

Item # 664

L20H80/27K

1	LAMP SPECIFICATION				
1-1	Lamp Type	LED H80			
1-2	Dimmable (Y/N)	NO			
1-3	Base	E26			
1-4	Lamp Finish/Type	Н80			
1-5	Lamp Wattage	20W			
1-6	Wattage Comparison (FC on Floor	250 Incand. (55W CFL)			
1-7	Rated Average Life (hours) L70	50,000			
1-9	Reliable Operating Temperature	-4F to 113F			
2	Photometric Characteristics			CH	1.00
2-1	Initial Lumens	2300			
2-2	Centre Beam Candle Power (Cd)	TBA			
2-3	Beam Angle (50% I Max) in Degree	e 140			
2-4	Beam Angle (10% I Max) in Degree	e N/A		ETL CLASSIFIED	_
2-5	Initial Lumens per Watt	115		c us Ro	
2-6	Color Temperature	2700К		Intertek 5003348	pliant
2.7	Color Rendering Index (CRI)	80			
3	Electrical Characteristics				
3-1	Input Line Voltage/Frequency	120V/277V 50/60 Hz	3-2	Power Factor	>0.90
3-3	Lamp rated Wattage	20W	3-4	Input Line Current	180mA(120V) 80mA(277V)
3-5	Total Harmonic Distortion	<30%(120V), <20% +(277V)	3-6	Dimming Range in %	Not Dimmable
4	Dimensional Characteristics				
4-1	Nominal Length (Inches/mm)	6.69" / 170 mm	4-2	Diameter	3.15" / 80 mm
5	Product Information				
5-1	Description	20W LED High Watt H80 Lamp - 2700K			
5-2	Primary Application	Commercial, Industrial, Agriculture			
5-3	Warranty	5 Years from date of purchase			
5-4	TCLP Compliant	YES	5-6	RoHS Compliant	YES
5-5	Energy Star or LM79 (Y/N)	ТВА	5-8	ETL	YES
6	PACKING DETAILS				
6-1	Color Box Size (Inches) 1x1	3.3 x 3.3 x 7.3	6-2	Inner Carton Size (Inches)	N/A
6-3	Master Carton Size (Inches) 1x12	14.17 x 10.63 x 7.87	6-4	Gross Weight / Net Weight (lbs)	8.49 / 5.61
01/2017© Overdrive For more information visit www.overdrive-lighting.com					

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.