



75W Low Bay LED Retrofit Lamp-5000K

Item # 668
L75T190 5000K

1 LAMP SPECIFICATION

1-1 Lamp Type	Low Bay LED Retrofit Lamp
1-2 Dimmable (Y/N)	No
1-3 Base	E39
1-4 Lamp Finish/Type	Long Neck T190
1-5 Lamp Wattage	75W
1-6 Wattage Comparison (FC on Floor)	upto 175W HID
1-7 Rated Average Life (hours) L70	50,000
1-9 Reliable Operating Temperature	-4°F to 113°F



2 Photometric Characteristics

2-1 Initial Lumens	7500
2-2 Centre Beam Candle Power (Cd)	1950
2-3 Beam Angle (50% I Max) in Degree	125
2-4 Beam Angle (10% I Max) in Degree	165
2-5 Initial Lumens per Watt	100
2-6 Color Temperature	5000K
2.7 Color Rendering Index (CRI)	80

3 Electrical Characteristics

3-1 Input Line Voltage/Frequency	120V/277V- 50/60Hz	3-2 Power Factor	>0.9
3-3 Lamp rated Wattage	75W	3-4 Input Line Current	710mA@120V 320mA@277V
3-5 Total Harmonic Distortion	≤20%	3-6 Dimming Range in %	Non Dimmable

4 Dimensional Characteristics

4-1 Nominal Length (Inches/mm)	10.826 / 275	4-2 Diameter (Inches/mm)	7.480 / 190
--------------------------------	--------------	--------------------------	-------------

5 Product Information

5-1 Description	75W Low Bay LED Retrofit Lamp-5000K		
5-2 Primary Application	Commercial and Industrial use		
5-3 Warranty	5 Years from date of purchase		
5-4 TCLP Compliant	YES	5-6 RoHS Compliant	YES
5-5 Energy Star or LM79 (Y/N)	DLC/LM79	5-8 UL / FCC	YES

6 PACKING DETAILS

6-1 Color Box Size (Inches)	1x1	7.9 X 7.9 X 11.14	6-2 Inner Carton Size (Inches)	N.A
6-3 Master Carton Size (Inches)	1x4	16.34 X 16.34 X 12.20	6-4 Gross weight / Net weight (lbs)	10.14 / 6.39

01/2017© Overdrive For more information visit www.overdrive-lighting.com

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.