Uverdrive [®] LED by Innovation		6.5W LED High CRI R20 Dimmable - 2700K		20 Iten	ltem # 681 L6HR20DIM/27K	
				L6HR2		
1	LAMP SPECIFICATION		_			
1-1	Lamp Type	LED R20				
1-2	Dimmable (Y/N)	YES				
1-3	Base	E26				
1-4	Lamp Finish/Type	R20				
1-5	Lamp Wattage	6.5W				
1-6	Wattage Comparison (FC on Floor)	45W R20				
1-7	Rated Average Life (hours) L70	25,000				
1-9	Reliable Operating Temperature	-4F to 113F				
2	Photometric Characteristics Øverdrive					
2-1	Initial Lumens	450				
2-2	Centre Beam Candle Power (Cd)	150		2 - 2		
2-3	Beam Angle (50% I Max) in Degree	107			3	
2-4	Beam Angle (10% I Max) in Degree	NA				
2-5	Initial Lumens per Watt	69				
2-6	Color Temperature	2700K		energited		
2.7	Color Rendering Index (CRI)	90		ENERGY STAR		
3	Electrical Characteristics					
3-1	Input Line Voltage/Frequency	120V 60 Hz	3-2	Power Factor	0.9	
3-3	Lamp rated Wattage	6.5W	3-4	Input Line Current	60 mA	
3-5	Total Harmonic Distortion	32%	3-6	Dimming Range in %	Full	
4	Dimensional Characteristics		_			
4-1	Nominal Length (Inches/mm)	3.94" / 100 mm	4-2	Diameter	2.48" / 63 mm	
5	Product Information		_			
5-1	Description	6.5W LED 90 CRI R20 Dimmable - 2700K				
5-2	Primary Application	Household Use, Office & Commercial				
5-3	Warranty	5 Years from date of purc	chase			
5-4	TCLP Compliant	YES	5-6	RoHS Compliant	YES	
5-5	Energy Star or LM79 (Y/N)	ES	5-8	UL / FCC	YES	
6	PACKING DETAILS					
6-1	Color Box Size (Inches) 1x1 2.	6 x 2.6 x 4.3	6-2	Inner Carton Size (Inches)	NA	
6-3	Master Carton Size (Inches) 1x12 11	1.38 x 8.58 x 5.51	6-4	Gross Weight / Net Weight (lbs)	2.73 / 1.54	
02/2017© Overdrive For more information visit www.overdrive-lighting.com						
Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.						