

5W LED CRI 90 Candle Dimmable E12 - 2700K

ltem # 688

L5HCDDIM/E12/27K

1					
1	LAMP SPECIFICATION				
	Lamp Туре	LED CANDLE			
	Dimmable (Y/N)	YES		/	
1-3	Base	E12			
1-4	Lamp Finish/Type	CANDLE			
1-5	Lamp Wattage	5W			
1-6	Wattage Comparison (FC on Floor)	40W Candle			
1-7	Rated Average Life (hours) L70	25,000		and the second s	
1-8	LED Type	Seoul			
1-9	Reliable Operating Temperature	-4F to 113F			
2	Photometric Characteristics		_	6,	rerdrive
2-1	Initial Lumens	325			
2-2	Centre Beam Candle Power (Cd)	NA			
2-3	Beam Angle (50% I Max) in Degree	280		Alfal	
2-4	Beam Angle (10% I Max) in Degree	NA			
2-5	Initial Lumens per Watt	65			
2-6	Color Temperature	2700К		energy	
2.7	Color Rendering Index (CRI)	90		ENERGY STAR	
3	Electrical Characteristics				
3-1	Input Line Voltage/Frequency	120V 60Hz	3-2	Power Factor	0.91
3-3	Lamp rated Wattage	5W	3-4	Input Line Current	45 mA
3-5	Total Harmonic Distortion	28%	3-6	Dimming Range in %	Full
4	Dimensional Characteristics				
4-1	Nominal Length (Inches/mm)	3.78" / 96 mm	4-2	Diameter	1.37" / 34.9 mm
5	Product Information				
5-1	Description	5W LED CRI 90 Candle Dimmable E12 - 2700K			
5-2	Primary Application	Household Use, Office & Commercial			
5-3	Warranty	5 Years from date of purchase			
5-4	TCLP Compliant	YES	5-6	RoHS Compliant	YES
5-5	Energy Star or LM79 (Y/N)	ES	5-8	UL / FCC	YES
6	PACKING DETAILS				
6-1	Color Box Size (Inches) 1x1	1.5 x 1.5 x 4.3	6-2	Inner Carton Size (Inches) 1x1	NA
6-3	Master Carton Size (Inches) 1x12	6.69 x 5.12 x 5.24	6-4	Gross Weight / Net Weight (lbs)	1.68 / 1.21
02/2017© Overdrive For more information visit www.overdrive-lighting.com					
Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.					