



6W LED A Bulb Dimmable - 5000K Wet Location With Gasket

Item # 732

L6SA19DIM/50K

| 1 LAMP SPECIFICATION | | | |
|-------------------------------|----------------------------------|---|---|
| 1-1 | Lamp Type | LED A Bulb Dimmable | |
| 1-2 | Dimmable (Y/N) | YES | |
| 1-3 | Base | E26 (Medium Base) | |
| 1-4 | Lamp Finish/Type | A19 Shape | |
| 1-5 | Lamp Wattage | 6W | |
| 1-6 | Wattage Comparison (FC on Floor) | 40W Incand | |
| 1-7 | Rated Average Life (hours) L70 | 25,000 | |
| 1-8 | Reliable Operating Temperature | -4F to 113F | |
| 1-9 | Wet Location Rated | YES | |
| 1-10 | Enclosed Fixture Rated | YES | |
| 2 Photometric Characteristics | | | |
| 2-1 | Initial Lumens | 545 | |
| 2-2 | Centre Beam Candle Power (Cd) | 145 | |
| 2-3 | Beam Angle (50% I Max) in Degree | 125 | |
| 2-4 | Beam Angle (10% I Max) in Degree | 210 | |
| 2-5 | Initial Lumens per Watt | 91 | |
| 2-6 | Color Temperature | 5000K | |
| 2-7 | Color Rendering Index (CRI) | >80 | |
| 3 Electrical Characteristics | | | |
| 3-1 | Input Line Voltage/Frequency | 120V 60 Hz | 3-2 Power Factor >0.90 |
| 3-3 | Lamp rated Wattage | 6W | 3-4 Input Line Current 55mA |
| 3-5 | Total Harmonic Distortion | 20% | 3-6 Dimming Range in % Full |
| 4 Dimensional Characteristics | | | |
| 4-1 | Nominal Length (Inches/mm) | 4.25" / 108 mm | 4-2 Diameter 2.36" / 60 mm |
| 5 Product Information | | | |
| 5-1 | Description | 6W LED A Bulb Dimmable, 5000K, Medium Base - Wet Location | |
| 5-2 | Primary Application | Household Use, Office, Agriculture & Commercial | |
| 5-3 | Warranty | 5 Years from date of purchase | |
| 5-4 | TCLP Compliant | YES | 5-6 RoHS Compliant YES |
| 5-5 | Energy Star or LM79 (Y/N) | LM79 | 5-8 UL / FCC YES |
| 6 PACKING DETAILS | | | |
| 6-1 | Color Box Size (Inches) | 1x1 2.44 x 2.44 x 4.72 | 6-2 Inner Carton Size (cm) 1x12 10.35 x 7.72 x 5.12 |
| 6-3 | Master Carton Size (Inches) | 1x48 16.50 x 11.14 x 11.81 | 6-4 Gross Weight / Net Weight (lbs) 12.08 / 7.50 |

