



10W LED A Bulb Dimmable - 3000K Wet Location with Gasket

Item # 733

L10SA19DIM/30K

1 LAMP SPECIFICATION

1-1	Lamp Type	LED A Bulb Dimmable
1-2	Dimmable (Y/N)	YES
1-3	Base	E26 (Medium Base)
1-4	Lamp Finish/Type	A19 Shape
1-5	Lamp Wattage	10W
1-6	Wattage Comparison (FC on Floor)	60W Incand
1-7	Rated Average Life (hours) L70	25,000
1-8	Reliable Operating Temperature	-4F to 113F
1-9	Wet Location Rated	YES
1-10	Enclosed Fixture Rated	YES



2 Photometric Characteristics

2-1	Initial Lumens	950
2-2	Centre Beam Candle Power (Cd)	235
2-3	Beam Angle (50% I Max) in Degree	125
2-4	Beam Angle (10% I Max) in Degree	215
2-5	Initial Lumens per Watt	95
2-6	Color Temperature	3000K
2-7	Color Rendering Index (CRI)	80

3 Electrical Characteristics

3-1	Input Line Voltage/Frequency	120V 60 Hz	3-2	Power Factor	>0.90
3-3	Lamp rated Wattage	10W	3-4	Input Line Current	95mA
3-5	Total Harmonic Distortion	20%	3-6	Dimming Range in %	Full

4 Dimensional Characteristics

4-1	Nominal Length (Inches/mm)	4.25" / 108 mm	4-2	Diameter	2.36" / 60 mm
-----	----------------------------	----------------	-----	----------	---------------

5 Product Information

5-1	Description	10W LED A Bulb Dimmable -3000K Wet Location with Gasket			
5-2	Primary Application	Household Use, Office, Agriculture & Commercial			
5-3	Warranty	5 Years from date of purchase			
5-4	TCLP Compliant	YES	5-6	RoHS Compliant	YES
5-5	Energy Star or LM79 (Y/N)	LM79	5-8	UL / FCC	YES

6 PACKING DETAILS

6-1	Color Box Size (Inches)	1x1	2.44 x 2.44 x 4.72	6-2	Inner Carton Size (cm) 1x12	10.35 x 7.72 x 5.12
6-3	Master Carton Size (Inches)	1x48	16.50 x 11.14 x 11.81	6-4	Gross Weight / Net Weight (lbs)	12.50 / 7.94

10/2020© Overdrive For more information visit www.overdrive-lighting.com

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.