

10W LED A Bulb Dimmable -5000K Wet Location With Gasket

ltem # 734

L10SA19DIM/50K

		Gaske	•		
1	LAMP SPECIFICATION				
1-1	Lamp Type	LED A Bulb Dimmable		F	
1-2	Dimmable (Y/N)	YES			
1-3	Base	E26 (Medium Base)			
1-4	Lamp Finish/Type	A19 Shape			
1-5	Lamp Wattage	10W			
1-6	Wattage Comparison (FC on Floor)	60W Incand			
1-7	Rated Average Life (hours) L70	25,000		Green	trive
1-8	Reliable Operating Temperature	-4F to 113			
1-9	Wet Location Rated	YES			
1-10	Enclosed Fixture Rated	YES			
2	Photometric Characteristics				
2-1	Initial Lumens	1050			
2-2	Centre Beam Candle Power (Cd)	260			
2-3	Beam Angle (50% I Max) in Degree	125			
2-4	Beam Angle (10% I Max) in Degree	215		c(UI)us	Rolls
2-5	Initial Lumens per Watt	105			Compliant
2-6	Color Temperature	5000K			
2.7	Color Rendering Index (CRI)	80			
3	Electrical Characteristics		_		
3-1	Input Line Voltage/Frequency	120V 60 Hz	3-2	Power Factor	>0.90
3-3	Lamp rated Wattage	10W	3-4	Input Line Current	95mA
3-5	Total Harmonic Distortion	20%	3-6	Dimming Range in %	Full
4	Dimensional Characteristics				
	Nominal Length (Inches/mm)	4.25" / 108 mm	4-2	Diameter	2.36" / 60 mm
5	Product Information		_		
5-1	Description	10W LED A Bulb Dimmable -5000K, Medium Base - Wet Location with Gasket			
5-2	Primary Application	Household Use, Office, Agriculture &	Commercia	l	
5-3	Warranty	5 Years from date of purchase			
5-4	TCLP Compliant	YES	5-6		YES
5-5	Energy Star or LM79 (Y/N)	LM79	5-8	UL / FCC	YES
6	PACKING DETAILS		_		
6-1	Color Box Size (Inches) 1x1	2.44 x 2.44 x 4.72	6-2	Inner Carton Size (cm) 1x12	10.35 x 7.72 x 5.12
		16.50 x 11.14 x 11.81	6-4	Gross Weight / Net Weight (lbs)	12.50 / 7.94
10/2020© Overdrive For more information visit www.overdrive-lighting.com					
Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.					