

6.5W LED A19 AG Lamp - 2700K (Non Dim) Wet Location with Gasket

Item # 790G

L6SNA19/27K

_		Casical				
1	LAMP SPECIFICATION					
1-1	Lamp Type	LED A19 Lamp				
1-2	Dimmable (Y/N)	No		€		
1-3	Base	E26 (Medium Base)		2	===	
1-4	Lamp Finish/Type	A19 Shape				
1-5	Lamp Wattage	6.5W				
1-6	Wattage Comparison	40W Incand.				
1-7	Rated Average Life (hours) L70	25,000			Wverdrive	
1-8	Reliable Operating Temperature	-4F to 113F				
1-9	Wet Location Rated	YES				
1-10	Enclosed Fixture Rated	YES				
2	Photometric Characteristics					
2-1	Initial Lumens	630				
2-2	Centre Beam Candle Power (Cd)	160				
2-3	Beam Angle (50%) in Degree	125				
2-4	Beam Angle (10% I Max) in Degree	210				
2-5	Initial Lumens per Watt	97		C L JUS (ompliant	
2-6	Color Temperature	2700K				
2-7	Color Rendering Index (CRI)	80				
3	Electrical Characteristics					
3-1	Input Line Voltage/Frequency	120V 60 Hz	3-2	Power Factor	>0.80	
3-3	Lamp rated Wattage	6.5W	3-4	Input Line Current	70mA	
3-5	Total Harmonic Distortion	55%	3-6	Dimming Range in %	No	
4	Dimensional Characteristics					
4-1	Nominal Length (Inches/mm)	4.25 Inch / 108mm	4-2	Diameter	2.36 inch/60mm	
5	Product Information					
5-1	Description	6.5W LED A19 AG Lamp, 2700K Medium Base - Non Dim With Gasket				
5-2	Primary Application	Household Use, Office, Agriculture & Commercial				
5-3	Warranty	5 Years from date of purchase				
5-4	TCLP Compliant	YES	5-6	RoHS Compliant	YES	
5-5	Energy Star or LM79 (Y/N)	LM79 only	5-7	UL / FCC	YES	
6	ACKING DETAILS					
6-1	Color Box Size (Inches) 1x1	2.44 x 2.44 x 4.72	6-2	Inner Carton Size (cm) 1x12	10.35 x 7.72 x 5.12	
6-3	Master Carton Size (Inches) 1x48	16.50 x 11.14 x 11.81	6-4	Gross Weight / Net Weight (lbs)	11.88 / 7.28	
	10/2020© Overdrive For more information visit www.overdrive-lighting.com					

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.